



Wider Ramps



Hydraulic Jack
Option



Gate Hold Backs



Trip Lever
Option



8" I Beam Frame



1/8" Fenders





- 10 Gauge Sides and Floor
- 24" High Sides
- 6'-9-1/2" and 6'-1-1/2" Inside Bed Widths
- 8" Cold Formed I Beam Frame
- Rubber Ride Axles
- Aluminum Tool Box w/Storage
- Scissors Hoist on 12' and 14' Lengths
- 11 Gauge Diamond Plate Fenders



Aluminum Tool Box with Storage Area



Heavy Duty Adjustable Coupler (4 bolt)



Scissors Hoist Standard on 12' & 14' (cylinder on 10')



Step for Bed Access



Tarp Option

STANDARD SPECIFICATIONS

sidewalls & floor	10 gauge (thickness of steel)
height of sidewall	24"
width inside body	73-1/2" & 81-1/2"
frame	8" cold formed I-beam
tool box	aluminum diamond plate w/storage area
gate	double acting with metering chains
fenders	1/8" steel diamond plate
hydraulic lift	scissors hoist 12' & 14' - cylinder 10'
hydraulic pump	power up/gravity down
suspension	rubber ride (low maintenance)
brakes	electric (all wheels)
tire & wheel	9950 GVWR - 15" 8 ply rated - 6 bolt 12000 & 14000 GVWR 16" 10 ply rated 8 bolt
jack	7000 lb. 10' & 12' - 10000 lb. 14'
coupler	2-5/16" adjustable (4 bolt)
safety chains	3/8" with latch hook
lights & wiring	LED lights & sealed wire harness
ramps	15-1/2" wide x 72" long
warranty	2 year limited (see warranty for details)
other standard features	step to access inside bed d-rings inside bed gate hold back latches

OPTIONS

available rating	9950, 12000 & 14000 GVWR
pinle ring	
tarp	
stake pockets	
trip lever (forward pull)	for tailgating
jack upgrade	7k to 10k (10k standard on 14' bumper pulls and all goosenecks)
jack upgrade	hydraulic jack (power up/power down)
wireless remote	operates hydraulics wirelessly
tire upgrade	radial tires (radial tires standard on 16")
aluminum wheels	
spare tire & wheel	

COLORS

black - red - charcoal

DUMP BODY VOLUME

length	width	volume (cubic yard)
10'	73-1/2"	4.5
10'	81-1/2"	5
12'	81-1/2"	6
14'	81-1/2"	7

FRAME & BODY SPECIFICATIONS

frame & tongue	body sides & floor	body cross members	body main rails	fenders
8" I-beam (cold formed)	10 gauge	3" channel	2" x 3" x 3/16" tube	1/8" diamond plate

WEIGHT SPECIFICATIONS by GVWR (gross vehicle weight rating)

Bumper Pull					Gooseneck				
length	width	9950	12000	14000	length	width	12000	14000	
10'	73-1/2"	3140 lb.	3400 lb.	n/a	n/a	n/a	n/a	n/a	
10'	81-1/2"	3420 lb.	3580 lb.	n/a	n/a	n/a	n/a	n/a	
12'	81-1/2"	3580 lb.	3840 lb.	3990 lb.	12'	81-1/2"	4430 lb.	4590 lb.	
14'	81-1/2"	n/a	3980 lb.	4140 lb.	14'	81-1/2"	4740 lb.	4900 lb.	

AXLE SPECIFICATIONS (rubber ride suspension)

GVWR	axle
9950	6000 lb. - 6 bolt - electric brakes (easy lube spindles)
12000	6000 lb. - 8 bolt - electric brakes (easy lube spindles)
14000	7000 lb. - 8 bolt - electric brakes (easy lube spindles)

Reinhart Trailer Sales
905-846-1071



MORITZ
TRAILERS & TRUCK BODIES

MORITZ INTERNATIONAL, INC.
665 North Main Street, Mansfield, Ohio 44902
Phone (419)526-5222 www.moritzint.com

MORITZ

TRAILERS & TRUCK BODIES

DLH SERIES



Taste and see that the Lord is good: blessed is the man that trusteth in him. Psalm 34:8 KJV

BUILT TO LAST
PERFORMANCE

TBA SERIES



FH SERIES



FH+10 SERIES



ULH+6 SERIES



TGL SERIES



ULH SERIES



UDC SERIES



LRA SERIES

